

T8 8W 2FT. BYP TITANIUM LED SERIES



PRO



BYPass

8W REPLACES



17W
Fluo.

60% Energy Savings

- Wide beam design: 310° light emitting area
- Suitable for use in totally enclosed fixtures
- End-to-end lighting with no dark spots
- Frosted glass tube for increased light diffusion efficiency
- Meets NSF requirements
- Built-in universal voltage driver - Bypass installation



50,000 H



UNIVERSAL



EFFICACY



WARRANTY



CRI (Ra)



ENCLOSED**




TUBE FEATURES

Extra Wide Beam Design - Frosted Glass Body

This lamp uses an innovative coated glass design that diffuses heat and light more evenly than plastic. As a result of its compact light engine, this lamp produces a light emitting area of 310°. This wider beam angle improves a fixture's total light distribution and creates a more complete lighting effect.



Lamp Front View




Lamp Back View

End-to-End Lighting - Micro-Designed Driver

GREEN CREATIVE




Other LED Tubes



The lamp's micro-designed driver is located within the tube end cap which allows for better thermal performance and no dark spots. The result is powerful and seamless light from end to end.

BYPASS INSTALLATION



- ⌚ Bypass ballast by cutting all wires as in Fig. A
- ⌚ Directly wire Live + Neutral on a single end as in Fig. B for single tube or as in Fig. C for multiple tubes
- ⌚ Replace shunted lamp holder with non-shunted one if applicable (Instant Start)
- ⌚ Existing fixture maintains original UL compliance thanks to UL1598C tube

SPECIFICATIONS

Product Model	28413 8T8/2F/830/BYP/R	28414 8T8/2F/835/BYP/R	28415 8T8/2F/840/BYP/R
Type	T8	T8	T8
Base	Medium Bi-Pin G13	Medium Bi-Pin G13	Medium Bi-Pin G13
Power (W)	8	8	8
Voltage - Frequency	120-277V 50-60Hz	120-277V 50-60Hz	120-277V 50-60Hz
Color Temp. (ANSI)	Warm White 3000K	Neutral White 3500K	Cool White 4000K
CRI (Ra)	82	82	82
Typical lumens (lm)	1000	1050	1050
Efficacy (LPW)	125	131	131
Light Emitting Area	310°	310°	310°
Beam Angle	160°	160°	160°
Dimmable	No	No	No
Power Factor	0.9	0.9	0.9
THD	<20%	<20%	<20%
Rated Lifetime - L70 (hrs.)	50,000	50,000	50,000
Dia. x MOL	1.14"x23.74"(29x603mm)	1.14"x23.74"(29x603mm)	1.14"x23.74"(29x603mm)
Weight (lb. / g)	0.36lb. / 165g	0.36lb. / 165g	0.36lb. / 165g

* Suitable for use in totally enclosed fixtures

** Suitable for damp locations. Not for use where directly exposed to the weather or water

*** Full installation guide and more details available on website